

# PANEL Printer

2inch printer **Porti-P30/P40/PP40/P60/PP60**



<P30>



<P40/PP40>



<P60/PP60>



## Features

- Ultra small size rack mount printer.
- Very silent printing thru direct thermal printing method
- High speed(50mm/sec)
- UART or TTL, Parallel(PP40, PP60 only) interface.
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.

## Applications

Test & Measurement, Transportation, Health care, ATM, Coupon, Self service, Kiosks, Electronic voting systems

# PANEL Printer

## Specifications

Item	Specification		
Model	<b>Porti-P30</b>	<b>Porti-P40/PP40</b>	<b>Porti-P60/PP60</b>
Printing method	Direct thermal line printing		
Characters per line	42cpl (MAX)		
Characters size	Eng : 9*24 dots, 12*24 dots / Kor : 16*24 dots [24*24 dots]		
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.		
Resolution	203 dpi, 8 dots/mm		
Print width	2-inch (48mm, 384 dots)		
Paper speed	50 mm/sec (MAX)		
Paper supplied	Thermal roll paper (57mm wide, 30Ø)	Thermal roll paper (57mm wide, 40Ø)	Thermal roll paper (57mm wide, 60Ø)
Dimensions	75 * 55 30.3 mm	80 * 75 * 40 mm	76 * 93 * 62 mm
Weight	102g	P40:153g / PP40:164.5g	P60:274g / PP60:285g
Interface	<ul style="list-style-type: none"> <li>· P30 / P40 / P60 : UART or TTL</li> <li>· PP40 / PP60 : UART or Parallel</li> </ul>		
Barcodes	1-dimension: Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension: PDF417, QR Code, DATA Matrix		
Receive buffer size	10K bytes	10K bytes	10K bytes
Input power	5VDC, Standby 60mA and Max 2.5A (P30, P40 only) 9VDC, Standby 60mA and Max 3A (Standard model) 12~24VDC, Standby 60mA and Max 3A (PP40, PP60 only)		



## < WOOSIM PANEL PRINTER SERIES >