

MOBILE Printer

2inch printer **Porti-SD40**

Serial impact dot matrix



Features

- Pocket size(97 * 109 * 44.7 mm)
- Light weight(350g) for true mobility.
- Serial Impact Dot Matrix
- 40 Columns (180 dots / line)
- Battery Indicator
- UART or TTL, Bluetooth Ver2.0 interface
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.
- Microsoft Windows 98/ME/XP/2000 compatible

Applications

Mobile POS, Field sales and service, Transportation, Hospitality, Parking, Utility billing, Safety, Material management.

Specifications

| Item | Specification |
|---------------------|---|
| Printing system | Serial Impact DOT Matrix system |
| Printing direction | Uni-directional printing |
| Inking | Dedication ink ribbon cartridge (black or purple) |
| Characters size | (4 + 0.5) * 8 Font, 40 columns |
| Optional Characters | Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request. |
| Print width | 46.8 mm, 180 dots / line |
| Paper feed pitch | 3.52 mm (10 dot line) |
| Paper supplied | 57.5 mm, Ordinary paper or specified pressure sensitive copying paper |
| Printing speed | 1.8 line / sec ± 20% |
| Dimensions | 97 * 109 * 44.7 mm |
| Weight | 350g |
| Interface | • UART or TTL • Bluetooth Ver2.0 |
| Barcodes | 1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix |
| Receive buffer size | 10K bytes |
| Battery | Rechargeable 7.4V DC , 1100mAh (Li-ion) |
| Battery duration | 1 hour continuous printing |
| Battery charger | Input (100~250VAC, 50~60Hz) Output(8.4VDC/0.8A), 4hours full charge time |