

Compact Entry-Level (2" mobile printer)

WSP-R241



Features

- Pocket size (79.5 X 114.3 X 43.5mm)
- Light weight (197.2g) for true mobility.
- High speed(100mm/sec, MAX)
- High resolution(203dpi : 8dots/mm)
- USB+Bluetooth Ver3.0
- Intuitive LED's indicate Power(on/off),Error, Bluetooth status, Battery status
- Support Magnetic Stripe Reader [option]
- Support text and graphic printing.
- Easier paper loading by CLAMSHELL design.
- One touch paper cover
- 1.5m drop test



Specification

Item	Specification
Printing method	Direct thermal line printing
Characters per line	Default : 42cpl (9x24), 32cpl (12x24) Option : 48cpl (8x16), 24cpl (16x24)
Characters size	Eng : 9x24 dots, 12x24 dots Kor : 16x24 dots [24x24 dots]
Optional Characters	Simplified/Traditional Chinese, Cyrillic, Greek, Japanese, Latin9 and Others upon request.
Print width	2-inch (48mm, 576dots)
Printing speed	100 mm/sec (MAX)
Dimensions	79.5 x 114.3 x 43.5mm (Standard) 79.5 x 118.2 x 43.5mm (MSR Option)
Interface	USB, Bluetooth Ver3.0
Paper supplied	Thermal roll paper (58mm wide, 40Ø), Paper thickness : 60±5µm
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix
Driver	Microsoft Windows XP / VISTA / 10 , Windows CE, Linux, Android, iOS SDK/driver compatible
Battery	Rechargeable 7.4V DC , 1100mAh (Li-ion)
Battery duration	1 hour continuous printing
MSR [option]	Triple tracks (1&2&3 tracks)
Battery charger	Input (100~250VAC, 50~60Hz) Output(8.4VDC/0.8A), 4hours full charge time
Sensors	Cover open Sensor, Paper end Sensor