

2INCH MOBILE PRINTER

PORTI-SC30

Features

- Pocket size(75.5 * 112 * 34.56 mm)
- Light weight(192g) for true mobility.
- Very silent printing thru direct thermal printing method
- High speed (80mm/sec, MAX)
- UART or TTL, Bluetooth interface.
- IrDA Ver1.0 (option), USB (option) interface.
- Support Magnetic Stripe Reader
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.



MSR (Magnetic Stripe Reader)



Compact design



Applications

Mobile POS, Field sales and service, Transportation, Hospitality, Parking, Utility billing, Safety, Material management.



Specification

Item	Specification
Printing method	Direct thermal line printing
Characters per line	42cpl (MAX)
Characters size	Eng : 9x24 dots, 12x24 dots Kor : 16x24 dots [24x24 dots]
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.
Resolution	203 dpi, 8 dots/mm
Print width	2-inch (48mm, 384 dots)
Printing speed	80 mm/sec (MAX)
Dimensions	75.5 x 112 x 34.56 mm
Weight	192g
Interface	<ul style="list-style-type: none"> • UART(RS-232C or TTL) • IrDA Ver1.0 or Bluetooth Ver2.1 + EDR • USB
Paper supplied	Thermal roll paper (57mm wide, 30Ø) , Paper thickness : 60±5µm
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix
Driver	Microsoft Windows XP / VISTA / 7 , Windows CE, Linux, Android OS driver compatible
Battery	Rechargeable 7.4V DC , 1130mAh (Li-ion)
Battery duration	1 hour continuous printing
MSR	1&2 or 2&3 Track Reading
Battery charger	Input (100~250VAC, 50~60Hz) Output(8.4VDC/0.8A), 4hours full charge time